

## **THERMAL-HYDRAULIC EXPERIMENTS ON THE TALL LBE TEST FACILITY**

**B.R. Sehgal, W.M. Ma, A. Karbojian**

Royal Institute of Technology (KTH)

10044 Stockholm, Sweden

### **Abstract**

In order to support ADS-related technologies, the thermal-hydraulic ADS lead-bismuth loop (TALL) was designed and constructed at KTH to investigate the heat transfer performance of different heat exchangers, and the thermal-hydraulic characteristics of natural and forced circulation flow under steady and transient conditions. The LBE loop is of full height and was scaled such that the prototypic (power/volume) ratio would represent the main components. So far, the forced convection and heat transfer of LBE through a straight tube heat exchanger and a U-tube heat exchanger have been accomplished and documented [1]. Transient experiments in the test facility are being conducted with reference to safety issues of ADS under the following conditions: a) startup and shutdown, b) loss of heat sink, c) loss of external driving head, d) heater trips, e) sudden change in power, and f) blockage in pipe. Preliminary tests were encouraging given the agreement of experimental data with RELAP5 analysis. More transient experiments and RELAP5 analysis will be performed in the future.

## **Introduction**

Accelerator-driven systems (ADS) have been proposed for the transmutation of long-lived actinides in nuclear waste. Lead-bismuth eutectic (LBE) is likely to be a leading candidate for both coolant and target of ADS because LBE has exceptional chemical, thermo-physical and neutronic properties, which are well-suited for nuclear coolant and spallation target applications. In particular, LBE has a low melting temperature (~125 C) and a very high boiling temperature (~1 670 C). It is chemically inert, does not react violently with air and water, and its spallation can yield close to 30 neutrons per 1 GeV proton. However, LBE is not compatible with common steels used in nuclear installations, which therefore, requires specific protective measures. Due to its high atomic number, the understanding of LBE flow and heat transfer is necessary for the thermal-hydraulic design of an ADS.

Motivated by the increasing interest in transmutation of nuclear waste by LBE-cooled ADS worldwide, a great amount of R&D activities have been or are being performed to address the basic aspects of LBE technology. The European Union is one of the key players in this campaign, with 13 projects in the area of P&T of the EURATOM Fifth Framework Programme (FP5). The Royal Institute of Technology (KTH) is actively participating in the activities concerned with R&D on ADS technologies. We are partners in both the PDS-XADS and TECLA projects of FP5. The project of Technology, Materials and Thermal-hydraulics for Lead Alloys (TECLA) aims to validate the choice of LBE as the spallation material in the target and/or the coolant in a hybrid reactor. The key objective of TECLA is to investigate the corrosion phenomenon of the structural material with LBE and the thermal-hydraulic performance for LBE. We were involved in the medium-scale TECLA experiments on heat exchangers. According to the task, the thermal-hydraulic ADS lead-bismuth loop (TALL) was designed and constructed at KTH. Our guidelines for the design were not only to perform the experiments for heat exchangers, but also to establish an experimental platform for natural circulation and safety concerns in an LBE or lead-cooled reactor. As a result, the TALL facility was designed to perform transient experiments with reference to the safety issues of ADS.

The present paper focuses on a description of the TALL test facility, an overview of the investigation on heat exchangers and an introduction to ongoing transient experiments.

## **Description of the TALL test facility**

TALL is a medium-scale facility designed to perform investigations on LBE flow and heat transfer with prototypic thermal-hydraulic conditions (as in the conceptual ADS design). The flow can be forced convection or natural circulation in character. TALL can also be used to study the performance of a conceptual design during representative accident scenarios. The first objective of TALL was to perform experiments for TECLA, i.e. to investigate the heat transfer performance of different heat exchangers. The second objective was to investigate the thermal-hydraulic characteristics of LBE natural circulation and forced circulation flow under steady and transient conditions.

## ***Specifications***

The specifications of TALL are set and modified to simulate prototypic thermal-hydraulic conditions of an ADS reactor, with well-conditioned flow and controllable power for thermal-hydraulic tests. The facility consists of a primary loop (LBE loop) and a secondary loop (oil loop). The LBE loop consists of sump tank, core tank, expansion tank, heat exchanger, EM pump, EM flowmeter, electric heaters and instrumentation. It is 6.8-m tall and the placement of heaters and heat exchangers allows natural convection flow as should occur in the prototypic vessel. Scaling is based on two considerations – resources and conceptual ADS designs. The LBE loop is of full height and has been scaled to prototypic

(power/volume) ratio to represent all the components – their LBE volume, pressure drops, flow velocities and the heating rates corresponding to one tube of the chosen heat exchanger design. For the final design, partners and international collaborations provided the needed technological underpinning. The technical parameters are as follows.

- All parts in contact with LBE are made of 316 or 316 L stainless steel.
- The overall height of the facility is 6.8 m.
- Total electric power is 55 kW and can be increased.
- LBE flow velocity is up to 3 m/s in the heat exchanger.
- LBE volume flow rate is up to 2.5 m<sup>3</sup>/h.
- Maximum LBE temperature is up to 500°C.
- Maximum temperature difference along the heat exchanger is 150°C.
- The pressure at the top is ~1 bar and the bottom pressure is ~8 bar.
- Design natural convection velocity is »50 cm/s.
- The LBE is eutectic alloy with the composition of 45% Pb and 55% Bi in weight.
- LBE purity is higher than 99.5%.
- Oxygen level in LBE is measurable.
- The working fluid in secondary loop is glycerol [C<sub>3</sub>H<sub>5</sub>(OH)<sub>3</sub>] with a boiling point of 290°C.
- Configuration provides flexibility for different test sections.
- Data acquisition and control is provided.


### ***Main components***

TALL is composed of a primary loop and a secondary loop. The primary loop is a closed LBE loop consisting of a pump, flowmeter, oxygen meter, heaters, piping, heat exchangers and tanks. In addition, the facility has a data acquisition system, an oxygen measurement system, a cover gas system, a vacuum system and an exhaust system. The schema of the facility is depicted in Figure 1. The LBE operation and main components of the facility are described in detail in the text that follows.

For the first time only, LBE ingots are loaded into the melting tank, heated to 180°C and held 24 hours with argon flushing. Then, a scoop (fine mesh stainless steel) is used to clean the slag off the top of the LBE melt until the mirror surface shows and the molten LBE is transferred by drainage and argon pressure into the sump tank through the filter. During routine operation, the LBE is melted in the sump tank and pressurised to fill the loop. EM pump is used to circulate the molten LBE through the loop. After leaving the pump, the LBE flows through the core tank and is heated by immersion heaters to a specific temperature at the outlet, which is connected to a long vertical pipe. The LBE keeps travelling

up the long vertical pipe to the expansion tank where the LBE turns to the oxygen sensor and then through the heat exchanger where the LBE's temperature is decreased to a certain value. The LBE leaves the heat exchanger and keeps flowing down through the EM flowmeter, which is placed on the long vertical pipe between the heat exchanger and the pump. The LBE finally returns to the pump.

**Figure 1. Schema of the TALL test facility**



**Primary loop:**

Piping—33.4mm O.D. and 27.8mm I.D.  
 Material—AISI 316 stainless steel  
 Working fluid — LBE  
 Max flowrate — 15 liters/min  
 Preheating of piping — Rope heater

- 1—Valve for LBE
- 2—Core tank & heater (28kW)
- 3—Blind flange
- 4—Melting heater (6kW)
- 5—Sump tank for LBE
- 6—Observing window
- 7—Level sensor
- 8—Filter
- 9—Melting tank
- 10—Exhaust gas tank
- 11—HEPA filter
- 12—Expansion tank

**Secondary loop:**

Piping—26.7mm O.D. and 23.3mm I.D.  
 Piping material—carbon steel  
 Working fluid — Glycerol  
 Max flowrate — 260 liters/min  
 Preheating of piping — Band heater

- 13—Expansion tube
- 14—LBE-oil heat exchanger
- 15—EM Flowmeter
- 16—EM Pump
- 17—Oxygen meter
- 20—Oil-water heat exchanger
- 21—heater (3kW)
- 22—Sump tank for oil
- 23—Oil pump
- 24—Valve for oil
- 25—Flowmeter for oil

## *Tanks*

The melting tank is designed to melt commercial LBE ingots and to remove impurities. For preparation of the LBE melt, a round vessel is used. The melting tank was designed so that it can contain 150% of the loop's total volume with a certain free volume for cover gas plenum.

The sump tank collects the melted LBE from the melting tank before circulation. It has the same volume and diameter as the melting tank. It is placed under the loop so that it can collect and hold the LBE when the loop drains. An observation window is available on the top of the sump tank. During the operation, the LBE is melted in the sump tank and then transferred by cover gas pressure into the loop.

Two band heaters are employed to melt the LBE in each tank. The heaters are mounted around the outside surface of the vessel and are well-insulated. The LBE's temperature is controlled automatically by the controllable power supply system.

The highest located component of the loop is the expansion tank, which is used to collect the extra LBE from the loop due to heat expansion and to balance the pressure variation. All three tanks mentioned above are made of 316 stainless steel.

The core tank is one of the complicated components in the loop. It holds the immersion heaters that provide the main electric power supply. The core tank was scaled so that it could represent the reactor core corresponding to one tube of the heat exchanger, especially from the aspects of flow resistance and coolant inventory. Multi-hole plates are placed in the tank in order to increase the flow resistance. The number of the multi-hole plates can be changed in order to obtain the prototypic ratio of the core tank resistance to the loop's resistance. The immersion heaters are located in the lower part and the multi-hole plates are located in the upper part.

## *Heat exchanger*


According to a sub-task of TECLA, the thermal-hydraulic performance of different types of heat exchangers will be investigated.

As shown in Figure 2, straight tube and U-tube heat exchangers were designed to perform the TECLA experiments.

Geometrical scaling is done in order to preserve relevant non-dimensional parameters ( $Re$  for forced circulation and  $Gr$  for natural convection) and is based on resources (such as laboratory condition, instrumentation and budget). As a result, single tube heat exchangers were employed. Both heat exchangers are composed of an inner tube and an outer duct, with the primary fluid (LBE) flowing in the inner tube and the secondary fluid (glycerol) flowing in the annulus. For the ease of fabrication, a square duct is chosen as the outer duct of the U-tube heat exchanger.

A 10-mm I.D. and 1.5-mm thick steel tube is used as the inner tube in both the heat exchangers. LBE velocities and  $Re$  numbers similar to those in the heat exchanger of the conceptual ADS design are easy to reach in the experiments. The effective lengths of both heat exchangers are one meter, which was decided after comprehensive consideration of the inlet/outlet temperature, heat removal capacity, heat flux and flow resistance.

**Figure 2. Schema of the heat exchangers**



### *EM Pump*

The electromagnetic (EM) pump provides the driving head for forced convection flow. The pump uses a system of rotating permanent magnets, which can withstand an LBE temperature of 300°C to 450°C as in our application. The LBE flows through the channel located in the gap between these magnets. An AC motor is employed to rotate the pump, on the shaft of which two magnetic disks are fixed.

The pump can develop 1.6 bar pressure at the flow rate of 0.6 L/s. Productivity of the pump is controlled by adjusting the rotation speed of the motor using a standard frequency converter.

### *Secondary loop*

As shown in Figure 1, a secondary loop was designed to realise the heat transfer from LBE to an intermediate fluid, and finally to an oil-water heat exchanger. Glycerol [C<sub>3</sub>H<sub>5</sub>(OH)<sub>3</sub>] was chosen as the working fluid (intermediate fluid) in the secondary loop because it has a high boiling point (290 °C) and well known thermal properties. Glycerol's boiling point is much higher than the melting point of LBE (125 °C), which can also allow a higher operational temperature (± 125 °C) so that solidification of LBE in the heat exchanger is avoided.

The secondary loop is an open circulation loop that consists of an oil pump, heat exchangers, sump tank, flowmeter, piping, valves and assorted temperature and pressure sensors. The oil pump is employed for the secondary loop to supply the flow driving head. During the operation, the glycerol leaves the oil sump tank due to suction of the pump. After leaving the pump, the flow is divided into two parts – one part returns to the sump tank via the bypass and the other part keeps flowing and turns up to a flowmeter where the flow rate is recorded. The bypass design is for easy control of the flow rate. The glycerol leaving the flowmeter travels through a long vertical pipe and arrives at the heat exchanger, where the glycerol's temperature is increased due to heat received from the LBE. The glycerol leaves the heat exchanger, keeps flowing and turns down through the long vertical pipe and comes to another heat exchanger (oil-water heat exchanger) where the glycerol is cooled down by tap water and finally returns to the oil sump tank.

## Instrumentation

The EM flowmeter is designed for measuring the flow rate of liquid LBE in a 316 stainless steel pipe with a diameter of 30 mm. The flowmeter consists of a sensor, an electronic block and a cable connecting the sensor with the electronic block.

The sensor is mounted vertically around the cold leg under the heat exchanger. The signal from the sensor is processed by an electronic block and the reading is shown on a PC monitor. The liquid LBE's temperature at the sensor can reach up to 400 C. The measuring range of the flowmeter varies from 0.01 L/s to 1.0 L/s.

In order to monitor the oxygen level in LBE, an oxygen measurement system is employed. The system consists of an oxygen sensor (from Los Alamos National Laboratory, USA) and a Keithley 6 514 programmable electrometer.

A Rosemount 3 051 differential pressure transmitter in combination with the 1 199 diaphragm seal system is employed to measure the pressure drop of LBE flow.

An Omega FLMH-1 040 (AL)-HT high temperature oil flowmeter is used to measure the glycerol flow rate. Its temperature limit is up to 204 C. The flowmeter utilises a spring-and-piston type assembly, which enables it to be mounted in any position and gives immunity from changes in viscosity.

Thermocouples and pressure transducers are used to measure temperature and pressure, respectively. Electrical panels are available to control all operations of heaters, pumps and valves. A data acquisition system (DAS) is realised using National Instruments data input instrumentation and a computer program written in LabVIEW. The readings are performed through two SCXI-1 102 32-channel amplifiers and a 6 035E analogue input DAQ card.

## Tests on the heat exchangers

The facility came into operation in September 2003. Tests on a straight tube and a U-tube heat exchanger have since been conducted. The ranges of the main thermal-hydraulic parameters of LBE in a heat exchanger are: inlet temperature from 230 C to 450 C, temperature drop from 20 C to 100 C, and velocity from 0.5 m/s to 2.5 m/s. The pressure drop and heat transfer characteristics were obtained for the straight tube heat exchanger and the U-tube heat exchanger, respectively.

Figure 3 shows the variation of the pressure drop with the Reynolds number for the two tested heat exchangers. It is obvious that the pressure drop of the LBE flow through the U-tube is larger than that of the straight tube.

For LBE flow in a straight tube, it appears that the present measured values are on average 15% higher than those from the following Techo, *et al.*, correlation, which is for fully developed turbulent flow and smooth surface conditions.


$$\frac{1}{\sqrt{f}} = 1.7372 \ln \frac{\text{Re}}{1.964 \text{Re} - 3.8215} \quad (1)$$

For a commercial stainless steel tube, if roughness may be chosen as 0.018 mm, the pressure drop calculated by the following Moody correlation will be in reasonable agreement with experimental data.


$$f = 1.375 \cdot 10^{-3} \left[ 1 + 21.544 \left( \frac{2e}{d} + \frac{100}{Re} \right)^{1/3} \right] \quad (2)$$

For both heat exchangers, the overall heat transfer coefficient increases with the increasing LBE and glycerol flow rate (illustrated in Figures 4 and 5), but the glycerol flow rate has a more significant effect. Furthermore, the overall heat transfer coefficient of the U-tube heat exchanger is higher than that obtained in the straight tube heat exchanger under the same conditions. More details of tests on heat exchangers are documented in Ref. [1].

**Figure 3. Pressure drops of LBE flow through the heat exchangers**




**Figure 4. Effect of the glycerol flow rate on heat transfer**





**Figure 5. Effect of the LBE flow rate on heat transfer**



### Transient tests

Transient experiments with reference to safety issues of ADS were started in May 2004. While simulating decay heat in the core tank, the temperature and flow rate characteristics will be measured during the following transients:


- Startup or shutdown of the facility.
- Loss of heat sink (switch off pump in secondary loop).
- Loss of external driving head (switch off pump in primary loop) – completely passive mode of LBE loop operation.
- Switch on and off the heater to simulate accelerator trips.
- Blockage in pipes.
- Sudden increase or decrease in power.

It was deemed important to find a way to measure low velocity during LOF transients. As a result, the flowmeter was recalibrated and the correlation between flow rate and pressure drop through the heat exchanger was obtained, which provides a sound basis to monitor the flow change during the transients.


Based on improved measurement, a loss of flow transient is shown in Figure 6. The transient was stopped at 628 seconds since the temperature was reaching the limit. The variations of flow rate and temperature were very similar to the RELAP5 calculations as shown in Figure 7, which provides an encouraging perspective on the experiment and calculations, though they started from different initial conditions. If a new model of an EM pump is taken into account and the same initial conditions are used, we believe that the experiment and calculations will show good quantitative comparison.

The transient experiments are just at the beginning. More experiments will be performed during the next few months. A RELAP5 analysis will also be performed.

**Figure 6. The transient of loss of external driving head in the primary loop**



**Figure 7. Calculation of the transient of loss of external driving head in the primary loop**



### Concluding remarks

The TALL facility was designed to investigate transients with reference to safety issues as well as the thermal-hydraulic performance of heat exchangers in a conceptual ADS subcritical reactor design. Thus, it is a multi-purpose test platform. The facility came into operation in September 2003. So far, investigations have been performed on two different heat exchangers, one with a straight tube and one with a U-tube. Transient experiments addressing safety issues of the ADS are on the way. More data on transients and natural circulation will be obtained during the next several months. According to test progress, the main conclusions are as follows:

- The loop is well-controlled and the thermal-hydraulic conditions can be adjusted properly.
- The operational parameters, e.g. LBE flow rate and temperature level, meet design requirements.
- The LBE inlet temperatures of the heat exchangers are up to 450 C, with the outlet temperature of the core tank up to 500 C.

- Pressure drop through the straight tube appears to be higher than that calculated via the Techo, *et al.*, correlation (1) for a smooth tube, but in good agreement with that calculated via the Moody correlation (2), which takes into account the effect of surface roughness.
- The heat transfer coefficient of secondary (glycerol) flow is much smaller than that of primary (LBE) flow, and hence dominates the determination of the overall heat transfer coefficient.
- In general, the U-tube heat exchanger has a better heat transfer performance than the straight tube heat exchanger, especially for secondary flow. In fact, the heat transfer resistance is very low for primary flow, thus any heat transfer enhancement design should be put on the secondary side.
- Preliminary tests are encouraging for the agreement of experimental data with RELAP5 analysis.
- More experiments, data check and analysis will be carried out.

#### *Acknowledgements*

This work was supported by the European Commission (EC), the Swedish Nuclear Power Inspectorate (SKI) and the Swedish Nuclear Fuel and Waste Management Company (SKB).

#### **REFERENCES**

- [1] Sehgal, B.R., W. Ma, A. Karbojian, *Lead-bismuth Flow and Heat Transfer Performance in Heat Exchangers*, Technical Report for European Commission Fifth Framework Programme, Deliverable D39 of TECLA, December 2003.
- [2] Sehgal, B.R., W. Ma, Z. Koszela, A. Karbojian, *Thermal-hydraulic ADS Lead-bismuth Loop (TALL) and Pre-test Analysis*, Technical Report for European Commission Fifth Framework Programme, KTH, March 2003.
- [3] Kakac, S., *et al.*, *Handbook of Single-phase Convective Heat Transfer*, John Wiley & Sons (1987).
- [4] *Proceedings of the 2<sup>nd</sup> International Conference on Accelerator-driven Transmutation Technologies and Applications*, Kalmar, Sweden, 3-7 June 1996.
- [5] *Proceedings of Heavy Liquid Metal Coolants in Nuclear Technology*, Obninsk, Russia, 5-9 October (1998).
- [6] *XADS Pb-Bi Cooled Experimental Accelerator Driven System Reference Configuration*, Summary Report of Ansaldo Nucleare, ADS 1 SIFX 0500-Rev. 0 (2001).

- [7] *Energy Amplifier Demonstration Facility Reference Configuration*, Summary Report of Ansaldo Nucleare, EA B0.00 1 200-Rev. 0 (1999).
- [8] Buongiorno, J., *et al.*, *Thermal Design of Lead-bismuth Cooled Reactors for Actinide Burning and Power Production*, Massachusetts Institute of Technology, MIT-ANP-TR-066 (1999).

## TABLE OF CONTENTS

Foreword .....	3
Executive Summary.....	11
Welcome.....	15
<i>D-S. Yoon</i> Congratulatory Address .....	17
<i>I-S. Chang</i> Welcome Address .....	19
<i>G.H. Marcus</i> OECD Welcome .....	21
<b>GENERAL SESSION: ACCELERATOR PROGRAMMES AND APPLICATIONS.....</b>	<b>23</b>
<b><i>CHAIRS: B-H. CHOI, R. SHEFFIELD</i></b>	
<i>T. Mukaiyama</i> Background/Perspective.....	25
<i>M. Salvatores</i> Accelerator-driven Systems in Advanced Fuel Cycles .....	27
<i>S. Noguchi</i> Present Status of the J-PARC Accelerator Complex .....	37
<i>H. Takano</i> R&D of ADS in Japan.....	45
<i>R.W. Garnett, A.J. Jason</i> Los Alamos Perspective on High-intensity Accelerators.....	57
<i>J-M. Lagniel</i> French Accelerator Research for ADS Developments.....	69
<i>T-Y. Song, J-E. Cha, C-H. Cho, C-H. Cho, Y. Kim, B-O. Lee, B-S. Lee, W-S. Park, M-J. Shin</i> Hybrid Power Extraction Reactor (HYPER) Project .....	81

<i>V.P. Bhatnagar, S. Casalta, M. Hugon</i> Research and Development on Accelerator-driven Systems in the EURATOM 5 <sup>th</sup> and 6 <sup>th</sup> Framework Programmes.....	89
<i>S. Monti, L. Picardi, C. Rubbia, M. Salvatores, F. Troiani</i> Status of the TRADE Experiment.....	101
<i>P. D'hondt, B. Carlucci</i> The European Project PDS-XADS “Preliminary Design Studies of an Experimental Accelerator-driven System”.....	113
<i>F. Groeschel, A. Cadiou, C. Fazio, T. Kirchner, G. Laffont, K. Thomsen</i> Status of the MEGAPIE Project.....	125
<i>P. Pierini, L. Burgazzi</i> ADS Accelerator Reliability Activities in Europe .....	137
<i>W. Gudowski</i> ADS Neutronics .....	149
<i>P. Coddington</i> ADS Safety .....	151
<i>Y. Cho</i> Technological Aspects and Challenges for High-power Proton Accelerator-driven System Application.....	153
<b>TECHNICAL SESSION I: ACCELERATOR RELIABILITY.....</b>	<b>163</b>
<b><i>CHAIRS: A. MUELLER, P. PIERINI</i></b>	
<i>D. Vandeplasseche, Y. Jongen (for the PDS-XADS Working Package 3 Collaboration)</i> The PDS-XADS Reference Accelerator .....	165
<i>N. Ouchi, N. Akaoka, H. Asano, E. Chishiro, Y. Namekawa, H. Suzuki, T. Ueno, S. Noguchi, E. Kako, N. Ohuchi, K. Saito, T. Shishido, K. Tsuchiya, K. Ohkubo, M. Matsuoka, K. Sennyu, T. Murai, T. Ohtani, C. Tsukishima</i> Development of a Superconducting Proton Linac for ADS.....	175
<i>C. Miélot</i> Spoke Cavities: An Asset for the High Reliability of a Superconducting Accelerator; Studies and Test Results of a $\beta = 0.35$ , Two-gap Prototype and its Power Coupler at IPN Orsay .....	185
<i>X.L. Guan, S.N. Fu, B.C. Cui, H.F. Ouyang, Z.H. Zhang, W.W. Xu, T.G. Xu</i> Chinese Status of HPPA Development .....	195

<i>J.L. Biarrotte, M. Novati, P. Pierini, H. Safa, D. Uriot</i> Beam Dynamics Studies for the Fault Tolerance Assessment of the PDS-XADS Linac .....	203
<i>P.A. Schmelzbach</i> High-energy Beat Transport Lines and Delivery System for Intense Proton Beams .....	215
<i>M. Tanigaki, K. Mishima, S. Shiroya, Y. Ishi, S. Fukumoto, S. Machida, Y. Mori, M. Inoue</i> Construction of a FFAG Complex for ADS Research in KURRI .....	217
<i>G. Ciavola, L. Celona, S. Gammino, L. Andò, M. Presti, A. Galatà, F. Chines, S. Passarello, XZh. Zhang, M. Winkler, R. Gobin, R. Ferdinand, J. Sherman</i> Improvement of Reliability of the TRASCO Intense Proton Source (TRIPS) at INFN-LNS .....	223
<i>R.W. Garnett, F.L. Krawczyk, G.H. Neuschaefer</i> An Improved Superconducting ADS Driver Linac Design.....	235
<i>A.P. Durkin, I.V. Shumakov, S.V. Vinogradov</i> Methods and Codes for Estimation of Tolerance in Reliable Radiation-free High-power Linac .....	245
<i>S. Henderson</i> Status of the Spallation Neutron Source Accelerator Complex .....	257
<b>TECHNICAL SESSION II: TARGET, WINDOW AND COOLANT TECHNOLOGY.....</b>	<b>265</b>
<b>CHAIRS: X. CHENG, T-Y. SONG</b>	
<i>Y. Kurata, K. Kikuchi, S. Saito, K. Kamata, T. Kitano, H. Oigawa</i> Research and Development on Lead-bismuth Technology for Accelerator-driven Transmutation System at JAERI .....	267
<i>P. Michelato, E. Bari, E. Cavaliere, L. Monaco, D. Sertore, A. Bonucci, R. Giannantonio, L. Cinotti, P. Turroni</i> Vacuum Gas Dynamics Investigation and Experimental Results on the TRASCO ADS Windowless Interface .....	279
<i>J-E. Cha, C-H. Cho, T-Y. Song</i> Corrosion Tests in the Static Condition and Installation of Corrosion Loop at KAERI for Lead-bismuth Eutectic .....	291
<i>P. Schuurmans, P. Kupschus, A. Verstrepen, J. Cools, H. Ait Abderrahim</i> The Vacuum Interface Compatibility Experiment (VICE) Supporting the MYRRHA Windowless Target Design .....	301

<i>C-H. Cho, Y. Kim, T-Y. Song</i> Introduction of a Dual Injection Tube for the Design of a 20 MW Lead-bismuth Target System.....	313
<i>H. Oigawa, K. Tsujimoto, K. Kikuchi, Y. Kurata, T. Sasa, M. Umeno, K. Nishihara, S. Saito, M. Mizumoto, H. Takano, K. Nakai, A. Iwata</i> Design Study Around Beam Window of ADS.....	325
<i>S. Fan, W. Luo, F. Yan, H. Zhang, Z. Zhao</i> Primary Isotopic Yields for MSDM Calculations of Spallation Reactions on <sup>280</sup> Pb with Proton Energy of 1 GeV.....	335
<i>N. Tak, H-J. Neitzel, X. Cheng</i> CFD Analysis on the Active Part of Window Target Unit for LBE-cooled XADS.....	343
<i>T. Sawada, M. Orito, H. Kobayashi, T. Sasa, V. Artisyuk</i> Optimisation of a Code to Improve Spallation Yield Predictions in an ADS Target System.....	355
<b>TECHNICAL SESSION III: SUBCRITICAL SYSTEM DESIGN AND ADS SIMULATIONS.....</b>	<b>363</b>
<b><i>CHAIRS: W. GUDOWSKI, H. OIGAWA</i></b>	
<i>T. Misawa, H. Unesaki, C.H. Pyeon, C. Ichihara, S. Shiroya</i> Research on the Accelerator-driven Subcritical Reactor at the Kyoto University Critical Assembly (KUCA) with an FFAG Proton Accelerator.....	365
<i>K. Nishihara, K. Tsujimoto, H. Oigawa</i> Improvement of Burn-up Swing for an Accelerator-driven System .....	373
<i>S. Monti, L. Picardi, C. Ronsivalle, C. Rubbia, F. Troiani</i> Status of the Conceptual Design of an Accelerator and Beam Transport Line for Trade.....	383
<i>A.M. Degtyarev, A.K. Kalugin, L.I. Ponomarev</i> Estimation of some Characteristics of the Cascade Subcritical Molten Salt Reactor (CSMSR).....	393
<i>F. Roelofs, E. Komen, K. Van Tichelen, P. Kupschus, H. Ait Abderrahim</i> CFD Analysis of the Heavy Liquid Metal Flow Field in the MYRRHA Pool.....	401
<i>A. D'Angelo, B. Arien, V. Sobolev, G. Van den Eynde, H. Ait Abderrahim, F. Gabrielli</i> Results of the Second Phase of Calculations Relevant to the WPPT Benchmark on Beam Interruptions .....	411



**TECHNICAL SESSION IV: SAFETY AND CONTROL OF ADS ..... 423**

**CHAIRS: J-M. LAGNIEL, P. CODDINGTON**

*P. Coddington, K. Mikityuk, M. Schikorr, W. Maschek,  
R. Sehgal, J. Champigny, L. Mansani, P. Meloni, H. Wider*  
Safety Analysis of the EU PDS-XADS Designs..... 425

*X-N. Chen, T. Suzuki, A. Rineiski, C. Matzerath-Boccaccini,  
E. Wiegner, W. Maschek*  
Comparative Transient Analyses of Accelerator-driven Systems  
with Mixed Oxide and Advanced Fertile-free Fuels ..... 439

*P. Coddington, K. Mikityuk, R. Chawla*  
Comparative Transient Analysis of Pb/Bi  
and Gas-cooled XADS Concepts ..... 453

*B.R. Sehgal, W.M. Ma, A. Karbojian*  
Thermal-hydraulic Experiments on the TALL LBE Test Facility ..... 465

*K. Nishihara, H. Oigawa*  
Analysis of Lead-bismuth Eutectic Flowing into Beam Duct..... 477

*P.M. Bokov, D. Ridikas, I.S. Slessarev*  
On the Supplementary Feedback Effect Specific  
for Accelerator-coupled Systems (ACS)..... 485

*W. Haeck, H. Ait Abderrahim, C. Wagemans*  
 $K_{\text{eff}}$  and  $K_s$  Burn-up Swing Compensation in MYRRHA ..... 495

**TECHNICAL SESSION V: ADS EXPERIMENTS AND TEST FACILITIES ..... 505**

**CHAIRS: P. D'HONDT, V. BHATNAGAR**


*H. Oigawa, T. Sasa, K. Kikuchi, K. Nishihara, Y. Kurata, M. Umeno,  
K. Tsujimoto, S. Saito, M. Futakawa, M. Mizumoto, H. Takano*  
Concept of Transmutation Experimental Facility ..... 507

*M. Hron, M. Mikisek, I. Peka, P. Hosnedl*  
Experimental Verification of Selected Transmutation Technology and Materials  
for Basic Components of a Demonstration Transmuter with Liquid Fuel  
Based on Molten Fluorides (Development of New Technologies for  
Nuclear Incineration of PWR Spent Fuel in the Czech Republic) ..... 519

*Y. Kim, T-Y. Song*  
Application of the HYPER System to the DUPIC Fuel Cycle..... 529

*M. Plaschy, S. Pelloni, P. Coddington, R. Chawla, G. Rimpault, F. Mellier*  
Numerical Comparisons Between Neutronic Characteristics of MUSE4  
Configurations and XADS-type Models ..... 539

<i>B-S. Lee, Y. Kim, J-H. Lee, T-Y. Song</i> Thermal Stability of the U-Zr Fuel and its Interfacial Reaction with Lead .....	549
<b>SUMMARIES OF TECHNICAL SESSIONS .....</b>	<b>557</b>
<b><i>CHAIRS: R. SHEFFIELD, B-H. CHOI</i></b>	
<i>Chairs: A.C. Mueller, P. Pierini</i> Summary of Technical Session I: Accelerator Reliability .....	559
<i>Chairs: X. Cheng, T-Y. Song</i> Summary of Technical Session II: Target, Window and Coolant Technology .....	565
<i>Chairs: W. Gudowski, H. Oigawa</i> Summary of Technical Session III: Subcritical System Design and ADS Simulations.....	571
<i>Chairs: J-M. Lagniel, P. Coddington</i> Summary of Technical Session IV: Safety and Control of ADS .....	575
<i>Chairs: P. D'hondt, V. Bhatagnar</i> Summary of Technical Session V: ADS Experiments and Test Facilities.....	577
<b>SUMMARIES OF WORKING GROUP DISCUSSION SESSIONS .....</b>	<b>581</b>
<b><i>CHAIRS: R. SHEFFIELD, B-H. CHOI</i></b>	
<i>Chair: P.K. Sigg</i> Summary of Working Group Discussion on Accelerators.....	583
<i>Chair: W. Gudowski</i> Summary of Working Group Discussion on Subcritical Systems and Interface Engineering .....	587
<i>Chair: P. Coddington</i> Summary of Working Group Discussion on Safety and Control of ADS.....	591
<i>Annex 1: List of workshop organisers .....</i>	<i>595</i>
<i>Annex 2: List of participants.....</i>	<i>597</i>



**From:**

## **Utilisation and Reliability of High Power Proton Accelerators**

Workshop Proceedings, Daejeon, Republic of Korea, 16-19 May 2004

**Access the complete publication at:**

<https://doi.org/10.1787/9789264013810-en>

### **Please cite this chapter as:**

Ma, W. M. (2006), "Thermal-Hydraulic Experiments on the Tall LBE Test Facility", in OECD/Nuclear Energy Agency, *Utilisation and Reliability of High Power Proton Accelerators: Workshop Proceedings, Daejeon, Republic of Korea, 16-19 May 2004*, OECD Publishing, Paris.

DOI: <https://doi.org/10.1787/9789264013810-47-en>

This work is published under the responsibility of the Secretary-General of the OECD. The opinions expressed and arguments employed herein do not necessarily reflect the official views of OECD member countries.

This document and any map included herein are without prejudice to the status of or sovereignty over any territory, to the delimitation of international frontiers and boundaries and to the name of any territory, city or area.

You can copy, download or print OECD content for your own use, and you can include excerpts from OECD publications, databases and multimedia products in your own documents, presentations, blogs, websites and teaching materials, provided that suitable acknowledgment of OECD as source and copyright owner is given. All requests for public or commercial use and translation rights should be submitted to [rights@oecd.org](mailto:rights@oecd.org). Requests for permission to photocopy portions of this material for public or commercial use shall be addressed directly to the Copyright Clearance Center (CCC) at [info@copyright.com](mailto:info@copyright.com) or the Centre français d'exploitation du droit de copie (CFC) at [contact@cfcopies.com](mailto:contact@cfcopies.com).